



**Specifications Noxion LED Panel Louvre 38W 3230lm - 840 Cool White | 120x30cm - UGR <15 - Philips Xitanium Driver - GST18 Male**

[View Product](#)

## General Information

|                          |                                                                                          |
|--------------------------|------------------------------------------------------------------------------------------|
| SKU                      | 223532                                                                                   |
| EAN                      | 8719157001113                                                                            |
| Brand                    | Noxion                                                                                   |
| Manufacturer Name        | Noxion LED Louvre 38W 4000K 86 L/W 30x120 Polish reflector GST18i3 connect. (2x36W eqv.) |
| Any Lamp all-in warranty | 6 Years                                                                                  |
| Average Lifetime (h)     | 50000                                                                                    |
| Series                   | Louvre Excell                                                                            |

## Technical Information

|                             |                 |
|-----------------------------|-----------------|
| Technology                  | LED Integrated  |
| Replaces (Watt)             | 2x36            |
| Wattage                     | 38              |
| Voltage (V)                 | 220-240         |
| Dimmable                    | Not Dimmable    |
| Colour Code                 | 840 Cool White  |
| Colour temperature (Kelvin) | 4000 Cool White |
| Colour Rendering (Ra)       | 80-89           |
| Colour of Light             | White           |
| Light colour options        | Single Color    |
| Including bulb              | Yes             |

|                          |                           |
|--------------------------|---------------------------|
| Light Distribution       | Symmetrical               |
| Luminous Flux (Lumen)    | 3230                      |
| Luminous Efficacy (lm/W) | 85                        |
| Suitable for Outdoor     | No                        |
| IP-rating                | IP20                      |
| Impact Protection (IK)   | IK02 - 0.20 joule         |
| Fixture Connection       | GST18i3 (2x1mm) male 0.5m |
| Installation Depth (mm)  | 55                        |
| Finish of Reflector      | Aluminium                 |
| Driver Included          | Yes                       |
| Power factor             | >0.95                     |
| Product Type Category    | LED Panel                 |

## Fixture Information

|                       |                                 |
|-----------------------|---------------------------------|
| Mounting Method       | Recessed                        |
| Unified Glare Rating  | < 15 - for special applications |
| Optical Cover         | PMMA (Polymethyl methacrylate)  |
| Operating Temperature | -10 to +40                      |
| Emergency Lighting    | No Emergency Unit               |
| Colour of the Fixture | White                           |
| Housing               | Aluminium                       |
| Colour of material    | White                           |

## Dimensions

|                |          |
|----------------|----------|
| LED panel size | 120x30cm |
| Length (mm)    | 1195     |
| Width (mm)     | 295      |

|             |    |
|-------------|----|
| Height (mm) | 55 |
|-------------|----|

## Sensor Information

---

Type of sensor

No Sensor

## Why Any-lamp?



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process



Trustpilot

