



**Specifications Noxion LED Panel Delta Pro Pronox V3.0 30W 3960lm - 830 Warm White | 60x60cm - UGR <22 - Dali Dimmable**

[View Product](#)

## General Information

|                          |                                                                                                   |
|--------------------------|---------------------------------------------------------------------------------------------------|
| SKU                      | 244336                                                                                            |
| EAN                      | 8719157036733                                                                                     |
| Brand                    | Noxion                                                                                            |
| Manufacturer Name        | Noxion LED Panel Delta Pro V3 DALI 30W 3000K 3960lm 60x60cm UGR <22   Warm White - Replaces 4x18W |
| Any Lamp all-in warranty | 6 Years                                                                                           |
| Average Lifetime (h)     | 50000                                                                                             |
| Series                   | Delta Pro                                                                                         |

## Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 4x18               |
| Wattage                     | 30                 |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 830 Warm White     |
| Colour temperature (Kelvin) | 3000 Warm White    |
| Colour Rendering (Ra)       | 80-89              |
| Colour of Light             | White              |
| Light colour options        | Single Color       |
| Including bulb              | Yes                |

|                          |                        |
|--------------------------|------------------------|
| Amount of bulbs required | 1                      |
| Luminous Flux (Lumen)    | 3960                   |
| Luminous Efficacy (lm/W) | 132                    |
| IP-rating                | IP20                   |
| Impact Protection (IK)   | IK03 - 0.35 joule      |
| Fixture Connection       | PI [Push-in connector] |
| Finish of Reflector      | Frosted                |
| Power factor             | >0.90                  |
| Product Type Category    | LED Panel              |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Recessed                       |
| Unified Glare Rating  | < 22 - for general areas       |
| Optical Cover         | PMMA (Polymethyl methacrylate) |
| Operating Temperature | -10 to +40                     |
| Emergency Lighting    | No Emergency Unit              |
| Colour of the Fixture | White                          |
| Housing               | Aluminium                      |
| Colour of material    | White                          |

## Dimensions

|                |         |
|----------------|---------|
| LED panel size | 60x60cm |
| Length (mm)    | 600     |
| Width (mm)     | 600     |
| Height (mm)    | 42      |

## Sensor Information

Type of sensor

No Sensor

### Why Any-lamp?



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process

